

SUBMITTAL DATA

GMV-ND30A/B-T(U) for use with VRF Outdoor Unit
24000 BTU/H Multi-Position Air Handler Unit

Job Name	Location	Date
Purchaser	Engineer	
Submitted to	For	
Unit Designation	Schedule No.	



GMV-ND30A/B-T(U)



XE70

GENERAL FEATURES


- Multi Position Air Handler W/ Multiple Fan Speed
- DC Inverter Motor
- Multiple Protections
- Ultra-low Noise Operation
- Up to 1.0 In W.C. Static Pressure
- Electric Heater Options
- XE70 Wired Controller Included
- Performance Based on Outdoor Unit
- Coil - Copper Tube / Aluminum Fin
- Blue Colored Fin - 500 Hrs Salt Spray Tested

SPECIFICATIONS, FEATURES & FUNCTION SUMMARY

SPECIFICATIONS		GMV-ND30A/B-T(U)	
System Type		HEAT PUMP	
SYSTEM PERFORMANCE			
Cooling	Nominal	Btu/h	30000
	Capacity @95°F	Btu/h	
Heating	Nominal	Btu/h	34000
	Capacity @5°F	Btu/h	
	Capacity @17°F	Btu/h	
	Capacity @47°F	W	
SEER2		System Performance Based on the Connected Outdoor Unit Performance	
EER2			
HSPF2			
COP @5°F			
COP @47°F			
Cooling Temperature Range			
Heating Temperature Range		°F	
Refrigerant Type		R410A	
INDOOR UNIT		GMV-ND30A/B-T(U)	
Air flow (Min-Max)		CFM	710 - 910
External Static Pressure (Default / Min - Max)		In W.c.	0.2 / 0~1.0
Sound Pressure Level (Min - Max)		dB(A)	40 - 44
Electric Heater (Optional)		kW	5, 8 , 10
Condensate Drain Size (OD)		in	1
External Dimensions (WxHxD)		in	18-1/8 x 43-1/2 x 21-1/4
Package Dimension (W x H x D)		in	20-3/8 x 46-1/8 x 24-3/8
Net Weight		lbs	123
Gross Weight		lbs	134
REFRIGERANT PIPING			
Line Set Sized by the Indoor Unit (Liquid - Gas)		in	3/8 - 5/8
ELECTRICAL			
Power Supply		208-230V / 1Ph / 60Hz (Powered by the Outdoor Unit)	
MCA		A	4
MOCP		A	15

FEATURES & FUNCTIONS SUMMARY	GMV-ND30A/B-T(U)
SYSTEM FEATURES	
Wired Controller Interface	Yes
WiFi Included	No
Easy Service Access	Yes
Indoor Fan Type	Centrifugal
Multi Fan Speeds	3 Speeds
Indoor Unit Display	No
Electrical Heater	Yes
Ventilation (Outdoor Air)	No
REMOTE CONTROLLER FUNCTIONS	
Auto Mode	Yes
Auto Fan	Yes
Auto Swing (Horizontal Auto Swing)	NO
Auto Swing - 180° (Vertical Auto Swing)	Yes
Clock	Yes
Dry Mode	Yes
Dry Anti-Mildew (X-Fan) Mode	Yes
Energy Saving Mode	Yes
Dirty Filter Alert	No
Fan Speed Control (7 Speeds)	Yes
I Feel Function	Yes
Privacy Lock	Yes
Quiet Mode	Yes
Room Temperature Display	No
Sleep Mode	Yes
3 Sleep Mode Options	Yes
Timer Mode	Yes
Turbo Mode	Yes
Display On/Off Control	Yes
Freeze Guard Mode	Yes
Power Failure Mode	Yes


FAN PERFORMANCE



NOTE:

The design range of the units air volume is from 710~910 CFM. The units would be damaged if they are used out of range.

ACCESSORY HEATER AND GENERAL INFORMATION




MODEL	Heat Kit Model	Electric Heat (kW)		Min. Circuit Ampacity (A)		Max. Fuse or Breaker (A)	
		208V	240V	208V	240V	208V	240V
GMV-ND30A/B-T(U)	FLEXXHTR5KW	3.74	5	22.6	26	25	30
	FLEXXHTR8KW	6.03	8	36	41.7	40	45
	FLEXXHTR10KW	7.51	10	45	52	45	60

DIMENSIONS & CLEARANCES

INDOOR UNIT

Unit: inch



GMV-ND30A/B-T(U)	
DIMENSIONS	
W	18-1/8
D	21-1/4
H	43-1/2
A	11-5/8
B	16-3/4



INDOOR UNIT

Minimum clearance

FRONT	> 24
-------	------



Horizontal Left Configuration - No Modification Needed



Horizontal Right Configuration - Must Relocate Drain Pan

NOTE:

Allow a minimum of 24" in front of the unit for service clearance. When installing in an area directly over a finished ceiling (such as an attic), an emergency drain pan is required directly under the unit. **See local and state codes for requirements.** When installing this unit in an area that may become wet, elevate the unit with a sturdy, non-porous material. In installations that may lead to physical damage (i.e. a garage) it is advised to install a protective barrier to prevent such damage. This air handler is designed for a complete supply and return ductwork system.



Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.